

# KLÍČ KLOUBOVÝ DO ČELNÍCH OTVORŮ / KLÍČ NA POVOLOVÁNÍ HYDRAULICKÝ VÁLCŮ



Hinged pin wrench straight, largest  $\varnothing$  / pin nominal  $\varnothing$ : 40/4mm



---

## Description

### Version:

Special steel, drive head ground, annealed and burnished.

With fixed pins.

### Application:

For twin hole nuts.

### Note:

Pin  $\varnothing$  = pin nominal  $\varnothing$  - 0.1 mm; tolerance field h12.

---

## Technical description

largest $\varnothing$	40 mm
Pin nominal $\varnothing$	4 mm
overall length	150 mm
Pin spacing adjustable a	18 - 40 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner

Klíče nejsou vhodné na povolování např. zarezlého víka válce



## Hinged pin wrench straight, largest $\varnothing$ / pin nominal $\varnothing$ : 80/4mm



---

### Description

**Version:**

Special steel, drive head ground, annealed and burnished.

With fixed pins.

**Application:**

For twin hole nuts.

**Note:**

Pin  $\varnothing$  = pin nominal  $\varnothing$  - 0.1 mm; tolerance field h12.

---

### Technical description

largest $\varnothing$	80 mm
Pin spacing adjustable a	40 - 80 mm
Pin nominal $\varnothing$	4 mm
overall length	220 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



## Hinged pin wrench straight, largest $\varnothing$ / pin nominal $\varnothing$ : 80/6mm



---

### Description

**Version:**

Special steel, drive head ground, annealed and burnished.

With fixed pins.

**Application:**

For twin hole nuts.

**Note:**

Pin  $\varnothing$  = pin nominal  $\varnothing$  - 0.1 mm; tolerance field h12.

---

### Technical description

Pin nominal $\varnothing$	6 mm
Pin spacing adjustable a	40 - 80 mm
overall length	220 mm
largest $\varnothing$	80 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



## Hinged pin wrench straight, largest $\varnothing$ / pin nominal $\varnothing$ : 125/6mm



---

### Description

**Version:**

Special steel, drive head ground, annealed and burnished.

With fixed pins.

**Application:**

For twin hole nuts.

**Note:**

Pin  $\varnothing$  = pin nominal  $\varnothing$  - 0.1 mm; tolerance field h12.

---

### Technical description

largest $\varnothing$	125 mm
Pin nominal $\varnothing$	6 mm
Pin spacing adjustable a	80 - 125 mm
overall length	295 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



## Hinged pin wrench straight, largest $\varnothing$ / pin nominal $\varnothing$ : 125/8mm



---

### Description

**Version:**

Special steel, drive head ground, annealed and burnished.

With fixed pins.

**Application:**

For twin hole nuts.

**Note:**

Pin  $\varnothing$  = pin nominal  $\varnothing$  - 0.1 mm; tolerance field h12.

---

### Technical description

overall length	295 mm
Pin spacing adjustable a	80 - 125 mm
largest $\varnothing$	125 mm
Pin nominal $\varnothing$	8 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner